



EVAC/PAVA System AP-D624EV 240W 6 Zone Voice Alarm Controller



AP-D624EV 240W 6 Zone Voice Alarm Controller

Features :

- Built-in 240W class-D amplifier
- Built in 6 zones with AB speaker Line and Low impedance monitor
- Max. capacity up 32 remotes paging microphone
- Expandable up to 120 zones by expansion routers
- Redundancy by the auto changeover standby amplifier
- Line supervision, Auto Changeover and Redundant amplifier option
- 2 Common inputs for Microphone/Line, Dedicated 4 Line in, 1 Rec out
- Third party system integration with Reset input, EVAC/Fault out
- Other interface such as SD card, fireman microphone
- Alarm & EVAC out, External amplifier interface
- LED Indicator for Fault, EVAC and Alert
- IP network integration module(optional)
- Dual RJ45 ports for remote paging microphone, router and dual Ports for LAN/WAN
- AC and DC operation, Power input 220VAC or DC-24V(Optional 110V)
- Fully integration EVAC controller, Paging system, Standard PA and BGM system

APPLICATIONS


Mall & Residential Apartments



Hotels & Hospital



Call Center/IT Parks



Technical Specifications

Model No.	AP-D624EV
Rated Power Output	240W
Inputs 1, 2	390mV, 10k Ω , MIC/Line In, Balanced
Inputs 3 ~ 6	350mV, 10k Ω , RCA
Frequency Response	80Hz ~ 20kHz
Rec Out	200mV
Speaker Output	100V, AB 6 Zone Speaker Out
Fireman Microphone	5mv, 600 Ω
S/N Ratio	>70dB
THD	<1%, 1KHz
Control Input	8 programmable Max 3.3V(voltage mode) or 0V closed contact
Control Output	8 programmable 0V closed contact, Fault & EVAC 0V closed contact, Reset Input 0V closed contact
Voice Record message	MP3/WMA format, max 255 messages, In SD-Card or by Player
Log Record	Last 10 years up to 1000 records
Power Input	200-260V AC, 24V DC, Fuse Protection(Optional 115V)
Power Consumption	300W
Working Temp. & Humidity	-5°C ~ 40°C, $\leq$ 95%RH (Not condensing)
Mount	19" Rack Mount, Table Top
Enclosure & Color	Full Metal, Black
Dimension & Weight	132(H) x 483(W) x 450(D) mm, <21Kg

